

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/053581 A1

(51) International Patent Classification⁷: A61F 2/46 B01F
13/00, 11/00, B05C 17/00

(21) International Application Number:

PCT/NL2004/000827

(22) International Filing Date:

29 November 2004 (29 11 2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/525,917

1 December 2003 (01 12.2003) US

(71) Applicant (for all designated States except US):
BROOCKEVILLE CORPORATION N.V. [NL/NL];
Landhuis Joonchi, Kaya Richard J Beaujon z/n, Willem-
stad, Curaçao (AN)

(72) Inventor; and

(75) Inventor/Applicant (for US only): DE VRIES, Jan, Al-
bert [NL/NL]; 6, Wolfersveenweg, NL-7021 HH Zelhem
(NL)


(74) Agent: VOLMER, J., C.; Exter Polak & Charlois B.V.,
P.O. Box 3241, NL-2280 GE Rijswijk (NL).

(81) Designated States (unless otherwise indicated for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, IR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated for every
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: A TOW-COMPONENT MIXING AND DISPENSING DEVICE



(57) Abstract: A device (10) for preparing and ejecting polymeric ce-
ment made from at least two pre-packaged components comprises a
tubular vessel (12) including a first axial end wall (14) having a closed
outlet (16), and a second axial end wall (18) having an aperture (20).
A first starting component (50) of the polymeric cement is present in-
side said tubular vessel near the first axial end wall (14). A shaft (22)
extends through said aperture (20) of the second axial end wall (18).
A piston element (34) comprises a closed container (36) filled with a
second starting component (46) of the polymeric cement. The piston
element (34) is selectively lockable to the shaft (22). The container has
a bore (38) and is slidingly engaged upon said shaft. An agitator ele-
ment (24) is secured to one end of the shaft (22). Furthermore opening
means (56) for providing an opening in the closed container (36) are
provided

WO 2005/053581 A1

BEST AVAILABLE COPY



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, IG)

Published:

— with international search report

For two-letter codes and other abbreviations refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette